

# Aluminium 2 S

Round holes Triangular pitch	Hole pattern Din 24 042			O.A %	1000 x 2000 Sheet thickness			1250 x 2500 Sheet thickness			1500 x 3000 Thickness		
	Rv	Ø	TD		mm			mm			mm		
	Rv	1,50	3,00	23	0,80			0,70					
	Rv	2,00	3,50	30	1,00								
	Rv	2,00	3,00	40	0,80	1,00							
	Rv	3,00	5,00	33	1,00	1,50							
	Rv	4,00	6,00	40	1,00								
	Rv	5,00	8,00	35	1,00	1,50	2,00						
	Rv	8,00	12,00	40	2,00								
	Rv	10,00	15,00	40	1,50	2,00	3,00						
	Rv	15,00	20,00	51	3,00								
Square holes Square pitch	Hole pattern Din 24 042			O.A %	1000 x 2000 Sheet thickness			1250 x 2500 Sheet thickness			1500 x 3000 Thickness		
	Qg	F	KD		mm			mm			mm		
	Qg	5,00	7,50	45	0,80	1,00	1,50	2,00				2,00	
	Qg	8,00	12,00	44	2,00								
	Qg	10,00	12,00	70	1,00	2,00			2,00				
Square holes Diagonal pitch	Hole pattern Din 24 042			O.A %	1000 x 2000 Sheet thickness			1250 x 2500 Sheet thickness			1500 x 3000 Thickness		
	Qv	F	DD		mm			mm			mm		
	Qv	8,00	17,00	44	1,50								
Round end slots Staggered lengthwise	Hole pattern Din 24 042			O.A %	1000 x 2000 Sheet thickness			1250 x 2500 Sheet thickness			1500 x 3000 Thickness		
	Lv	B	L		mm			mm			mm		
	Lv	5,00	25,00	50	1,50								

= External stock - app. 1-2 weeks delivery time